

PULSE TRAF0 12MH 3:1

€ 12,50

Excl. BTW: € 10,33

Afbeeldingen



Beschrijving

Features

- Single and double secondary winding
- Vacuum potting
- Allows high potential difference voltage scaling
- Very low partial discharge effects
- PCB through-hole mounting



Technical Specifications



Max. Operating Frequency: 40kHz

Temperature Range: -25...+70°C



Part Nr.	Transformation	I_{ign} [A]	L [mH]	R_{prim} [Ohm]	R_{sek} [Ohm]
IT213	1:1:1	0,25	6,5	1,4	1,4
IT233	1:1:1	0,25	3	0,8	0,8
IT239	1:1	0,25	3	0,9	0,9
IT242	1:1:1	0,1	2,5	0,75	0,75
IT243	1:1:1	0,1	2,5	0,8	0,8
IT244	3:1:1	0,1	15	2,8	0,9
IT245	1:1	0,1	8	1,48	1,48
IT246	2:1	0,1	7	2,1	1,1
IT248	2:1	0,25	17	3,2	1,6
IT249	2:1:1	0,25	17	3,1	1,5
IT253	1:1:1	0,25	1,1	0,55	0,55
IT255	1:1	0,25	2,2	0,8	0,8
IT258	1:1	1	2,5	0,62	0,75
IT260	3:1	0,1	12	2	0,8
IT313	1:1:1	1	3	0,33	0,4
IT314	3:1:1	1	35	1,6	0,7

I_{ign} = Ignition Current @ 40°C, L = Inductance, R_{prim} = Primary DC Resistance, R_{sec} = Secondary DC Resistance

Productinformatie

Artikelnummer	IT260
Merk	SCHAFFNER

