

Input Voltage:	90...264V AC (47...63Hz)
	127...370V DC
Input Inrush Current, Max.:	60A
Leakage Current, Max.:	2mA
Over Load Protection:	115...160%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight	
EPS-45-_:	140g
EPS-45-_-C:	300g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U _A	I _A	P _A	DU _A	U _{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
EPS-45-3.3	3,3	0...8	26,4	3	80	80
EPS-45-3.3-C	3,3	0...8	26,4	3	80	80
EPS-45-5	5	0...8	40	2	80	82
EPS-45-5-C	5	0...8	40	2	80	82
EPS-45-7.5	7,5	0...5,4	40,5	2	100	84
EPS-45-7.5-C	7,5	0...5,4	40,5	2	100	84
EPS-45-12	12	0...3,75	45	2	120	87
EPS-45-12-C	12	0...3,75	45	2	120	87
EPS-45-15	15	0...3	45	2	150	88
EPS-45-15-C	15	0...3	45	2	150	88

EPS-45-24	24	0...1,9	45,6	1	240	89
EPS-45-24-C	24	0...1,9	45,6	1	240	89
EPS-45-36	36	0...1,25	45	1	280	89
EPS-45-36-C	36	0...1,25	45	1	280	89
EPS-45-48	48	0...1	48	1	300	90
EPS-45-48-C	48	0...1	48	1	300	90

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

Artikelnummer	EPS4512
Merk	MEANWELL

