


## GESCHAKELDE VOEDING SINGLE OUTPUT 132W 3.3V/40A

€ 57,95

Excl. BTW: € 47,89

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile



#### Technical Specifications



Input Voltage:

88...264V AC (47...63Hz)

124...370V DC

Input Inrush Current, Max.:	40A
Leakage Current, Max.:	1mA
Output Voltage Adjustment:	±10%
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight:	720g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U <sub>A</sub>	I <sub>A</sub>	P <sub>A</sub>	DU <sub>A</sub>	U <sub>RN</sub>	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
RSP-200-2.5	2,5	0...40	100	2	100	79,5
RSP-200-3.3	3,3	0...40	132	2	100	81,5
RSP-200-4	4	0...40	160	2	100	84
RSP-200-5	5	0...40	200	2	150	85,5
RSP-200-7.5	7,5	0...26,7	200,25	2	150	89
RSP-200-12	12	0...16,7	200,4	1	150	89
RSP-200-13.5	13,5	0...14,9	201,15	1	150	89
RSP-200-15	15	0...13,4	201	1	150	89,5
RSP-200-24	24	0...8,4	201,6	1	150	89,5
RSP-200-27	27	0...7,5	202,5	1	200	89
RSP-200-36	36	0...5,56	200,16	1	220	90
RSP-200-48	48	0...4,2	201,6	1	240	90

U<sub>A</sub> = Output Voltage, I<sub>A</sub> = Output Current Range, P<sub>A</sub> = Output Power, U<sub>adj</sub> = Output Voltage Adjustment, DU<sub>A</sub> = Output Voltage Tolerance, U<sub>RN</sub> = Ripple & Noise, h = Efficiency

## Productinformatie

---

Artikelnummer	RSP20003
Merk	MEANWELL

