


**GESCHAKELDE VOEDING SINGLE OUTPUT 300W 3.3V/60A**

**€ 119,00**

Excl. BTW: € 98,35

**Afbeeldingen**



**Beschrijving**

**Features**

- Enclosed case, screw terminals
- Universal input
- Withstands 300V AC surge input for 5s
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Built-in remote sense function
- DC OK signal



**Technical Specifications**




Input Voltage:	85...264V AC (47...63Hz)
	120...370V DC
Input Inrush Current, Max.:	70A
Leakage Current, Max.:	1,2mA
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-40...+70°C
Weight:	950g

I/P = Input, O/P = Output, FG = Frame Ground



$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

Part Nr.	$U_A$	$I_A$	$P_A$	$U_{adj}$	$DU_A$	$U_{RN}$	$h$
	[V]	[A]	[W]	[V]	[%]	[mV <sub>p-p</sub> ]	[%]
HRP-300-3.3	3,3	0...60	198	2,8...3,8	2,5	80	80
HRP-300-5	5	0...60	300	4,3...5,8	2	90	82
HRP-300-7.5	7,5	0...40	300	6,8...9	2	100	86
HRP-300-12	12	0...27	324	10,2...13,8	1	120	88
HRP-300-15	15	0...22	330	13,5...18	1	150	88
HRP-300-24	24	0...14	336	21,6...28,8	1	150	87
HRP-300-36	36	0...9	324	28,8...39,6	1	250	88
HRP-300-48	48	0...7	336	40,8...55,2	1	250	89

  $U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Productinformatie

---

Artikelnummer	HRP30003
Merk	MEANWELL

