


## GESCHAKELDE VOEDING SINGLE OUTPUT 85W 5.0V/17A

€ 69,50

Excl. BTW: € 57,44

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, screw terminals
- Universal input
- Withstands 300V AC surge input for 5s
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- Built-in active PFC function
- Low profile
- Long life 105°C electrolytic capacitors
- Low no load power consumption
- Built-in remote On/Off control



#### Technical Specifications



Input Voltage:

85...264V AC (47...63Hz)

120...370V DC

Input Inrush Current, Max.:	65A
Leakage Current, Max.:	1mA
Over Load Protection:	105...135%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-40...+60°C
Weight:	560g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	$U_A$	$I_A$	$P_A$	$U_{adj}$	$DU_A$	$U_{RN}$	$h$
	[V]	[A]	[W]	[V]	[%]	[mV <sub>p-p</sub> ]	[%]
HRP-100-3.3	3,3	0...20	66	3,1...3,8	+2,5,-3,5	80	78
HRP-100-5	5	0...17	85	4,75...5,8	2,5	80	83
HRP-100-7.5	7,5	0...13,5	101,3	7,1...9	2,5	100	84
HRP-100-12	12	0...8,5	102	11,4...13,8	1,5	120	87,5
HRP-100-15	15	0...7	105	14,25...18	1,5	150	88
HRP-100-24	24	0...4,5	108	22,8...28,8	1,5	150	88,5
HRP-100-36	36	0...2,9	104,4	34,2...39,6	1,5	200	89
HRP-100-48	48	0...2,2	105,6	45,6...55,2	1,5	240	90

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $U_{adj}$  = Output Voltage Adjustment,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

## Productinformatie

---

Artikelnummer	HRP10005
Merk	MEANWELL
Is on Sale	Nee

