


## GESCHAKELDE VOEDING SINGLE OUTPUT 52W 48V/1.1A

**€ 16,95**

Excl. BTW: € 14,01

### Afbeeldingen



### Beschrijving

#### Features

- Enclosed case, screw terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low profile
- Safety standards: EN 62368-1
- EMC standards: EN 55032 Class B and more
- 3 years manufacturer warranty



#### Technical Specifications



Input Voltage:

85...264V AC (47...63Hz)

120...373V DC

|                             |             |
|-----------------------------|-------------|
| Input Inrush Current, Max.: | 45A         |
| Leakage Current, Max.:      | 0,75mA      |
| Output Voltage Adjustment:  | ±10%        |
| Over Load Protection:       | 110...150%  |
| Withstand Voltage           |             |
| I/P-O/P:                    | 3750V AC    |
| I/P-FG:                     | 2000V AC    |
| O/P-FG:                     | 1250V AC    |
| Operating Temperature:      | -30...+70°C |
| Operating Altitude, Max.:   | 5000m       |
| Weight:                     | 230g        |

I/P = Input, O/P = Output, FG = Frame Ground



| Part Nr.   | $U_A$ | $I_A$    | $P_A$ | $DU_A$ | $U_{RN}$             | $h$ |
|------------|-------|----------|-------|--------|----------------------|-----|
|            | [V]   | [A]      | [W]   | [%]    | [mV <sub>p-p</sub> ] | [%] |
| LRS-50-3.3 | 3,3   | 0...10   | 33    | 3      | 80                   | 80  |
| LRS-50-5   | 5     | 0...10   | 50    | 2      | 80                   | 83  |
| LRS-50-12  | 12    | 0...4,2  | 50,4  | 1      | 120                  | 86  |
| LRS-50-15  | 15    | 0...3,4  | 51    | 1      | 120                  | 88  |
| LRS-50-24  | 24    | 0...2,2  | 52,8  | 1      | 150                  | 88  |
| LRS-50-36  | 36    | 0...1,45 | 52,2  | 1      | 200                  | 89  |
| LRS-50-48  | 48    | 0...1,1  | 52,8  | 1      | 200                  | 90  |

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise,  $h$  = Efficiency

|               |          |
|---------------|----------|
| Artikelnummer | LRS5048  |
| Merk          | MEANWELL |

