

| | |
|-----------------------------|-------------|
| Input Inrush Current, Max.: | 45A |
| Leakage Current, Max.: | 0,75mA |
| Output Voltage Adjustment: | ±10% |
| Over Load Protection: | 110...150% |
| Withstand Voltage | |
| I/P-O/P: | 3750V AC |
| I/P-FG: | 2000V AC |
| O/P-FG: | 1250V AC |
| Operating Temperature: | -30...+70°C |
| Operating Altitude, Max.: | 5000m |
| Weight: | 230g |

I/P = Input, O/P = Output, FG = Frame Ground



| Part Nr. | U_A | I_A | P_A | DU_A | U_{RN} | h |
|-----------|-------|---------|-------|--------|----------------------|-----|
| | [V] | [A] | [W] | [%] | [mV _{p-p}] | [%] |
| LRS-35-5 | 5 | 0...7 | 35 | 2 | 80 | 82 |
| LRS-35-12 | 12 | 0...3 | 36 | 1 | 120 | 86 |
| LRS-35-15 | 15 | 0...2,4 | 36 | 1 | 120 | 86 |
| LRS-35-24 | 24 | 0...1,5 | 36 | 1 | 150 | 88 |
| LRS-35-36 | 36 | 0...1 | 36 | 1 | 200 | 88 |
| LRS-35-48 | 48 | 0...0,8 | 38,4 | 1 | 200 | 89 |

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | LRS3505 |
| Merk | MEANWELL |

