

## DIN-RAIL 40MM VOEDING 120W 24V/2.5A

€ 37,93

Excl. BTW: € 31,35

### Afbeeldingen



### Beschrijving

#### Features

- Direct assembly on DIN Rail
- Enclosed case, Touch-guard screw terminals
- Universal input
- Overload protection, current limiting, auto recovery
- Protections: short circuit/over load/over voltage
- DC OK LED display



#### Technical Specifications



Input Voltage:

90...264V AC (47...63Hz)

127...370V DC

Input Inrush Current, Typ.:	35A
Leakage Current, Max.:	1mA
Output Voltage Adjustment:	+15%
Over Load Protection:	105...130%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-20...+70°C
Weight:	600g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
<b>NDR-120-12</b>	12	0...10	120	2	100	85,5
<b>NDR-120-24</b>	24	0...5	120	1	120	88
<b>NDR-120-48</b>	48	0...2,5	120	1	150	89

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

Artikelnummer	NDR12048
Merk	MEANWELL

