

ZIJKNIPTANG 115MM 0,3-1,6MM PUNT

€ 45,25

Excl. BTW: € 37,40

Afbeeldingen



Beschrijving

Features

- Suitable for fine cutting work in electronics and fine mechanics
- Precision shaped tips also cut close sitting wire from 0,2mm
- Sturdy, through-put and zero-backlash box joint
- Handles with multi-component grips
- Made of special tool steel
- **KNIP7622-125**: Lap joint; made of Vanadium electric steel
- **KNIP7742-130** made of ball bearing chrome steel



### Cutting parameters

Part No.	Hardness [HRC]	Hard Wire Ø [mm]	Medium Hard Wire Ø [mm]	Soft Wire Ø [mm]
KNIP7722-115	57	-	1	0,3...1,3
KNIP7702-115	60	0,6	1,2	0,3...1,6
KNIP7742-115	57	-	0,8	0,3...1,3
KNIP7772-115	60	-	-	0,3...0,8
KNIP7622-125	63	-	-	0,4...2,5
KNIP7742-130	60	-	1,3	0,3...1,6



### Dimensions and Weight

Part No.	L x W x H [mm]	Weight [g]
KNIP7722-115	115 x 45 x 17	76
KNIP7702-115	115 x 71 x 48	76
KNIP7742-115	115 x 71 x 48	75
KNIP7772-115	115 x 50 x 17	74
KNIP7622-125	125 x 57 x 19	107
KNIP7742-130	130 x 61 x 18	122



### Surface and Type

Part No.	Head	Type
KNIP7722-115	Mirror polished	Round head, without bevel
KNIP7702-115	Mirror polished	Round head, with small bevel
KNIP7742-115	Mirror polished	Pointed head, without bevel
KNIP7772-115	Mirror polished	Pointed mini head, with small bevel
KNIP7622-125	Polished	Round head, without bevel
KNIP7742-130	Mirror polished	Pointed head, without bevel



### Norms

DIN ISO 9654  
 KNIP7622-125: DIN ISO 5749

### Productinformatie

Artikelnummer	KNIP7742-1
Merk	KNIPEX

