



	120...373V DC
Input Inrush Current, Max.:	65A
Leakage Current, Max.:	0,75mA
Output Voltage Adjustment:	±10%
Over Load Protection:	110...150%
Withstand Voltage	
I/P-O/P:	3750V AC
I/P-FG:	2000V AC
O/P-FG:	1250V AC
Operating Temperature:	-30...+70°C
Operating Altitude, Max.:	5000m
Weight:	300g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	$U_A$	$I_A$	$P_A$	$DU_A$	$U_{RN}$	h
	[V]	[A]	[W]	[%]	[mV <sub>p-p</sub> ]	[%]
LRS-75-5	5	0...14	70	2	100	86,5
LRS-75-12	12	0...6	72	1	120	89
LRS-75-15	15	0...5	75	1	120	89
LRS-75-24	24	0...3,2	76,8	1	150	90
LRS-75-36	36	0...2,1	75,6	1	200	91,5
LRS-75-48	48	0...1,6	76,8	1	200	91,5

$U_A$  = Output Voltage,  $I_A$  = Output Current Range,  $P_A$  = Output Power,  $DU_A$  = Output Voltage Tolerance,  $U_{RN}$  = Ripple & Noise, h = Efficiency

## Productinformatie

---

Artikelnummer	LRS7548
Merk	MEANWELL

