


GESCHAKELDE VOEDING SINGLE OUTPUT 40W 7.5V/5.4A

€ 22,95

Excl. BTW: € 18,97

Afbeeldingen



Beschrijving

Features

- Compact case, 4" x 2"
- Contact pin for nylon-crimp terminals
- Universal input
- Overload protection, pulsing hiccup shutdown, auto recovery
- Protections: short circuit/over load/over voltage
- Low no load power consumption
- Safety standards: UL62368-1, EN62368-1
- EMC standards: EN55032 Class B and more
- 3 years manufacturer warranty
- EPS-45-_: Open frame



Technical Specifications



Input Voltage:

90...264V AC (47...63Hz)

	127...370V DC
Input Inrush Current, Max.:	60A
Leakage Current, Max.:	2mA
Over Load Protection:	115...160%
Withstand Voltage	
I/P-O/P:	3000V AC
I/P-FG:	2000V AC
O/P-FG:	500V AC
Operating Temperature:	-30...+70°C
Weight	
EPS-45-_:	140g

I/P = Input, O/P = Output, FG = Frame Ground



Part Nr.	U_A	I_A	P_A	DU_A	U_{RN}	h
	[V]	[A]	[W]	[%]	[mV _{p-p}]	[%]
EPS-45-3.3	3,3	0...8	26,4	3	80	80
EPS-45-5	5	0...8	40	2	80	82
EPS-45-7.5	7,5	0...5,4	40,5	2	100	84
EPS-45-12	12	0...3,75	45	2	120	87
EPS-45-15	15	0...3	45	2	150	88
EPS-45-24	24	0...1,9	45,6	1	240	89
EPS-45-36	36	0...1,25	45	1	280	89
EPS-45-48	48	0...1	48	1	300	90

U_A = Output Voltage, I_A = Output Current Range, P_A = Output Power, DU_A = Output Voltage Tolerance, U_{RN} = Ripple & Noise, h = Efficiency

Artikelnummer	EPS4507
Merk	MEANWELL



Productinformatie