

## GESCHAKELDE VOEDING SINGLE OUTPUT 35W 15V/2.4A

€ 23,50

Excl. BTW: € 19,42

### Afbeeldingen



### Beschrijving

Universal AC input / Full range  
Protections: Short circuit/Over load/Over voltage  
Cooling by free air convection  
LED indicator for power on  
100% full load burn-in test  
All using 105  
Withstand 300VAC surge input for 5 second  
High operating temperature up to 70  
Withstand 5G vibration test  
High efficiency, long life and high reliability

MODEL RS-35-15

OUTPUT:

DC VOLTAGE 15V  
RATED CURRENT 2.4A  
CURRENT RANGE 0 ~ 2.4A  
RATED POWER 36W  
RIPPLE & NOISE (max.) 120mVp-p  
OUTPUT VOLTAGE ADJ. RANGE 13.5 ~ 16.5V  
VOLTAGE TOLERANCE +/-1.0%  
LINE REGULATION +/-0.5%  
LOAD REGULATION +/-0.5%  
SETUP, RISE TIME 500ms, 30ms/230VAC  
HOLD TIME (Typ.) 80ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC  
FREQUENCY RANGE 47 ~ 63Hz  
EFFICIENCY(Typ.) 83%  
AC CURRENT (Typ.) 0.8A/230VAC  
INRUSH CURRENT (Typ.) COLD START 33A/230VAC  
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power  
Protection type : Hiccup mode, recovers automatically after fault condition is removed  
OVER VOLTAGE 17.25 ~ 20.25V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 99\*82\*36mm (L\*W\*H)

## Productinformatie

---

Artikelnummer	RS3515
Merk	MEANWELL
Is on Sale	Nee

