

---

**GESCHAKELDE VOEDING SINGLE OUTPUT 480W 48V/10A**

**€ 162,49**

Excl. BTW: € 134,29

**Afbeeldingen**

---



**Beschrijving**

---

Universal AC input / Full range  
Built in active PFC function, PF>0.95  
Protections: Short circuit / Overload / Over voltage / Over temperature  
Forced air cooling by built-in DC fan  
High power density 5.18w/in  
Low profile:43mm thickness  
Built-in remote ON-OFF control  
Built-in remote sense function  
Active AC surge current limiting

MODEL SP-480-48

OUTPUT:  
DC VOLTAGE 48V  
RATED CURRENT 10A  
CURRENT RANGE 0 ~ 11A  
RATED POWER 480W  
RIPPLE & NOISE (max.) 240mVp-p

OUTPUT VOLTAGE ADJ. RANGE 41 ~ 56V  
VOLTAGE TOLERANCE +/-1.0%  
LINE REGULATION +/-0.2%  
LOAD REGULATION +/-0.5%  
SETUP, RISE TIME 1000ms, 80ms at full load  
HOLD TIME (Typ.) 18ms at full load

INPUT:

VOLTAGE RANGE 85 ~ 264VAC  
FREQUENCY RANGE 47 ~ 63Hz  
EFFICIENCY(Typ.) 89%  
AC CURRENT (Typ.) 3.5A/230VAC  
INRUSH CURRENT (Typ.) 40A/230VAC  
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 11.55 ~ 14.85A rated output power  
OVER VOLTAGE 57.6 ~ 67.2V Protection type : Shut down o/p voltage, re-power on to recover.

Dimensions 278\*127\*43mm (L\*W\*H)

## Productinformatie

---

Artikelnummer	SP48048
Merk	MEANWELL
Is on Sale	Nee

