

ADAPTER 15V 1660MA GESCHAKELD

€ 19,95

Excl. BTW: € 16,49

Afbeeldingen



Beschrijving

Features

- Plug-in switching power supply
- Universal AC input
- Class II power (without earth pin)
- Compact design
- Overload and short circuit protection
- LED for power on

Technical Specifications

- Operating Temperature: 0...+50°C
- storage Temperature: -20...+85°C
- MTBF: 500.000h/25°C
- Dimensions: 79x54x33mm
- Weight: 220g
- Cable Length: 1,8m
- Plug: Coaxial Plug
- Ø2,1 inner(+) x Ø5,5 outer(-)

Input

Input Voltage: 90...264V AC (47...63Hz)
Conducted Inteferece: EN 55022 (B), FCC 15 (B)
EN61000-3-2,-3-3,-4-2,-4-3,-4-4,-4-5,-4-6,-4-8,-4-11
Hold Up Time, 115V: 16ms
In-Rush Current 230V: 40A

Output Voltage, 15V
Output Voltage Tolerance 3%
Ripple & Noise, 100mV
Output Rated Current, 1.66A
DC Output Power, 25W
Efficiency, 77%
All Technical Specifications are Applicable to TU = 25°

Productinformatie

| | |
|---------------|----------|
| Artikelnummer | PSS1516 |
| Merk | MEANWELL |
| Is on Sale | Nee |

