

DC-DC CONVERTER 36-72V:24V 0.625A IN BEHUIZING

€ 20,95

Excl. BTW: € 17,31

Afbeeldingen



Beschrijving

15W Single Output DC-DC Converter
2:1 wide input range
Protections: Short circuit/Over load /voltage
Built-in EMI filter, low ripple noise
100% full load burn-in test
Low cost
High reliability

OUTPUT

DC VOLTAGE: 24V
RATED CURRENT: 0,625A
CURRENT RANGE: 0 ~ 0.625A
RATED POWER: 15W
RIPPLE & NOISE (max.) Note.2: 150mVp-p
VOLTAGE ADJ. RANGE: 21.6 ~ 26.4VDC
VOLTAGE TOLERANCE Note.3: +/- 1.0%
LINE REGULATION: +/- 0.2%
LOAD REGULATION: +/- 0.2%
SETUP, RISE, HOLD UP TIME: 2.5s, 50ms, --12VDC/24VDC/48VDC at full load

INPUT

VOLTAGE RANGE: 36 ~ 72VDC
INPUT EFFICIENCY (Typ.): 78%
DC CURRENT: 0.45A/48VDC

DIMENSION: 78x51x28mm (LxWxH)

Productinformatie

Artikelnummer	SD15C24
Merk	MEANWELL
Is on Sale	Nee

