

DIN 8P FEMALE PLASTIC

€ 1,50

Excl. BTW: € 1,24

Afbeeldingen



Beschrijving

1. Temperature range $-25 \text{ }^{\circ}\text{C}/+70 \text{ }^{\circ}\text{C}$
2. Materials
Body PA 6.6 GF, HB according to UL 94
Contact spring CuZn, undernickelated and tinned
CuSn, silvered
Sleeve steel, undercoppered and nickelated
Housing PE, HB according to UL 94
3. Mechanical data
Insertion force/contact $\approx 7 \text{ N}$
Withdrawal force/contact $\approx 1 \text{ N}$
Cable diameter 6.0 mm
Mating with DIN plugs S, XS
Connectable conductors solder terminal
max. section 0.34 mm²
4. Electrical data
Contact resistance $\approx 10 \text{ m}\Omega$ (earth contact $\approx 30 \text{ m}\Omega$)
Rated current 4 A
Rated voltage 34 V AC
Test voltage 500 V AC/60 s
Insulation resistance $> 10 \text{ G}\Omega$ (XK 52, 72, 82 $> 1 \text{ k}\Omega$)
1 measured with a polished steel pin, nominal thickness 1.5 mm)

Productinformatie

| | |
|---------------|--------|
| Artikelnummer | DNK08P |
| Merk | Merk |
| Is on Sale | Nee |

