

GESCHAKELDE VOEDING SINGLE OUTPUT 75W 12V/6,25A

€ 44,10

Excl. BTW: € 36,45

Afbeeldingen



Beschrijving

MODEL SP-75-12

OUTPUT:

DC VOLTAGE 12V

RATED CURRENT 6.25A

CURRENT RANGE 0 ~ 6.25A

RATED POWER 75W

RIPPLE & NOISE (max.) 80mVp-p

OUTPUT VOLTAGE ADJ. RANGE 11.4 ~ 13.2V

VOLTAGE TOLERANCE +/-2.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-0.5%

SETUP, RISE TIME 600ms, 60ms at full load

HOLD TIME (Typ.) 36ms at full load

INPUT:

VOLTAGE RANGE 85 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY(Typ.) 77%

AC CURRENT (Typ.) 0.7A/230VAC

INRUSH CURRENT (Typ.) COLD START 30A/230VAC

LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 105 ~ 150% rated output power

Protection type : Hiccup mode, recovers automatically after fault condition is

OVER VOLTAGE 13.8 ~ 16.2V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 179*97*33mm (L*W*H)

Productinformatie

Artikelnummer	SP7512
Merk	MEANWELL
Is on Sale	Nee

