

GESCHAKELDE VOEDING SINGLE OUTPUT 35W 12V/3.0A

€ 23,50

Excl. BTW: € 19,42

Afbeeldingen



Beschrijving

Universal AC input / Full range
Protections: Short circuit/Over load/Over voltage
Cooling by free air convection
LED indicator for power on
100% full load burn-in test
All using 105
Withstand 300VAC surge input for 5 second
High operating temperature up to 70
Withstand 5G vibration test
High efficiency, long life and high reliability

MODEL RS-35-12

OUTPUT:

DC VOLTAGE 12V
RATED CURRENT 3A
CURRENT RANGE 0 ~ 3A
RATED POWER 36W
RIPPLE & NOISE (max.) 120mVp-p
OUTPUT VOLTAGE ADJ. RANGE 10.8 ~ 13.2V
VOLTAGE TOLERANCE +/-1.0%
LINE REGULATION +/-0.5%
LOAD REGULATION +/-0.5%
SETUP, RISE TIME 500ms, 30ms/230VAC
HOLD TIME (Typ.) 80ms/230VAC at full load

INPUT:

VOLTAGE RANGE 88 ~ 264VAC
FREQUENCY RANGE 47 ~ 63Hz
EFFICIENCY(Typ.) 81%
AC CURRENT (Typ.) 0.8A/230VAC
INRUSH CURRENT (Typ.) COLD START 33A/230VAC
LEAKAGE CURRENT <2mA / 240VAC

PROTECTION:

OVER LOAD 110 ~ 150% rated output power
Protection type : Hiccup mode, recovers automatically after fault condition is removed
OVER VOLTAGE 13.8 ~ 16.2V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 99*82*36mm (L*W*H)

Productinformatie

Artikelnummer	RS3512
Merk	MEANWELL
Is on Sale	Nee

