

## GESCHAKELDE VOEDING SINGLE OUTPUT 52W 48V/1.1A

€ 26,50

Excl. BTW: € 21,90

### Afbeeldingen



### Beschrijving

MODEL RS-50-48

#### OUTPUT:

DC VOLTAGE 48V

RATED CURRENT 1.1A

CURRENT RANGE 0 ~ 1.1A

RATED POWER 52.8W

RIPPLE & NOISE (max.) 120mVp-p

OUTPUT VOLTAGE ADJ. RANGE 42 ~ 54V

VOLTAGE TOLERANCE +/-1.0%

LINE REGULATION +/-0.5%

LOAD REGULATION +/-0.5%

SETUP, RISE TIME 500ms, 20ms/230VAC

HOLD TIME (Typ.) 60ms/230VAC at full load

#### INPUT:

VOLTAGE RANGE 88 ~ 264VAC

FREQUENCY RANGE 47 ~ 63Hz

EFFICIENCY(Typ.) 86%  
AC CURRENT (Typ.) 0.8A/230VAC  
INRUSH CURRENT (Typ.) COLD START 33A/230VAC  
LEAKAGE CURRENT <2mA / 240VAC

**PROTECTION:**

OVER LOAD 110 ~ 150% rated output power

Protection type : Hiccup mode, recovers automatically after fault condition is

OVER VOLTAGE 55.2 ~ 64.8V Protection type : Hiccup mode, recovers automatically after fault condition is removed

Dimensions 99\*97\*36mm (L\*W\*H)

## Productinformatie

---

Artikelnummer	RS5048
Merk	MEANWELL
Is on Sale	Nee

